



GluDown, Inc.
Phone: (214) 504-2503
Fax: (972) 833-1012
www.gludown.com

GluDown® WaterGrip® Membrane Adhesive and Primer

Technical Data	March 2018
Product Description	GluDown WaterGrip Membrane Adhesive and Primer provides long open time and aggressive tack for bonding a wide variety of waterproofing materials.
Features	<ul style="list-style-type: none">• Bonds common waterproofing materials<ul style="list-style-type: none">○ Membrane types: roll-on, spray-on, peel & stick○ Foam board○ Drainage board• Long Open Time: 24 hours+• Aggressive, instant bond• Water resistant once dry• Dries clear
Packaging	Available in the following packaging types: <ul style="list-style-type: none">• 5 Gallon Pail (P/N: GD5110), 18 Pails per pallet
Technical Properties	<ul style="list-style-type: none">• Viscosity: 6,500 cps \pm 2,500• Solids: 69.0% \pm 2.5%• Color: White, Clear when dry• Yield: ~350-450 sq feet/gallon• Application Temperature: 40°F and rising to 100°F
Storage & Shelf Life	<ul style="list-style-type: none">• Keep containers closed when not in use• Shelf Life: 6 months• Rotate stock using oldest product first• Do not allow container to freeze
General Application	<ul style="list-style-type: none">• Apply product using clean roller to one surface• 9 to 11 mils thickness is required for proper coverage• Adhesive is ready when color changes from white to clear<ul style="list-style-type: none">○ Approximately 30 – 60 minutes from application○ Over application, temperature, and humidity can lengthen adhesive ready time• Bond substrates using firm and steady pressure

Use on Fluid Applied Membranes	<ul style="list-style-type: none"> • Many fluid applied membranes will attack adhesives. It is important to follow these instructions when bonding to these products. • The fluid membrane must be allowed to cure least 24 hours before applying adhesives. • Prepare surfaces by removing all debris, dirt, and dust. • Apply Sticky Strips horizontally across the top of the membrane area leaving a 0"-6" gap in between strips depending on application. For best results, install strips at the point where the top of the drain board plastic will touch the membrane. • Roll WaterGrip onto area below Sticky Strips, do not apply WaterGrip to Sticky Strips. • When WaterGrip is ready attach materials using heavy pressure.
---------------------------------------	---

Warranties	<p>GLUDOWN, INC. MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of any adhesive in a particular application. Given the variety of factors that can affect the use and performance of a GluDown, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose for the user's method of application.</p>
-------------------	--

Limitation of remedies & liability	<p>If the GluDown, Inc. product is proved to be defective, THE EXCLUSIVE REMEDY, AT GLUDOWN, INC. OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE GLUDOWN, INC. PRODUCT. GluDown, Inc. shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.</p>
---	--