



GluDown, Inc.  
 Phone: (214) 504-2503  
 Fax: (972) 833-1012  
 www.gludown.com

## GluDown® Sticky Strips – Technical Data

<b>Technical Data</b>	April 2018
<b>Product Description</b>	<p>GluDown® Sticky Strips are a double sided adhesive system packaged on a 36 foot roll, which is conveniently cut into efficient and easy to use sizes.</p> <p>Sticky Strips bond a wide variety of materials including concrete, plastic, foam board, wood, MDF, glass and more.</p> <p>The Sticky Strips unique adhesive system offers extreme temperature and chemical resistance, making them an excellent bonding solution for the toughest of jobs.</p>
<b>Features</b>	<ul style="list-style-type: none"> <li>• Sizes:           <ul style="list-style-type: none"> <li>○ GD2314: 1.75" x 4" strips on 36' roll (~106 strips/roll)</li> <li>○ GD2316: 2.75" x 4" strips on 36' roll (~106 strips/roll)</li> </ul> </li> <li>• 1 strip can support ~2+ square feet of material</li> <li>• Bonds common waterproofing materials           <ul style="list-style-type: none"> <li>○ Membrane types: roll-on, spray-on, peel &amp; stick</li> <li>○ Foam board</li> <li>○ Drainage board</li> </ul> </li> <li>• Excellent adhesion to concrete, plastic, foam board, wood, MDF, glass and more.</li> <li>• Long Open Time: 24 hours+</li> <li>• Aggressive, instant bond</li> <li>• Water resistant after materials are bonded</li> </ul>
<b>Packaging</b>	<p>Available in the following packaging types:</p> <ul style="list-style-type: none"> <li>• GD2314: 1.75" x 4" strips on 36' roll (~106 strips/roll)           <ul style="list-style-type: none"> <li>○ 24 rolls per case</li> </ul> </li> <li>• GD2316: 2.75" x 4" strips on 36' roll (~106 strips/roll)           <ul style="list-style-type: none"> <li>○ 16 rolls per case</li> </ul> </li> </ul>
<b>Technical Properties</b>	<ul style="list-style-type: none"> <li>• Size: 1.75" or 2.75" x 4" strips on 36' roll (~106 strips/roll)</li> <li>• 1 strip can support ~2+ square feet of material</li> <li>• Thickness: 1/32"</li> <li>• Application Temperature: 40°F and rising to 100°F</li> <li>• Service Temperature: -40°F to 180°F</li> </ul>
<b>Storage &amp; Shelf Life</b>	<ul style="list-style-type: none"> <li>• Store in a clean area free from exposure to excessive heat, moisture or direct sunlight (44% to 55% relative humidity, 50° to 80°F).</li> <li>• Shelf life under these conditions - one year.</li> </ul>

<p><b>Product Application</b></p>	<ul style="list-style-type: none"> <li>• Remove dust, debris, moisture from surfaces to be bonded</li> <li>• Apply necessary number of strips to first surface, then attach second substrate using firm and uniform pressure in areas with Sticky Strips.</li> <li>• Large surface area recommend pattern:             <ul style="list-style-type: none"> <li>○ Top of bonded area: Strips applied horizontally spaced 4 to 6 inches apart</li> <li>○ As necessary, add additional rows every 2 to 3 feet below the row above.                 <ul style="list-style-type: none"> <li>▪ Spacing in between Strips for additional rows can be increased to 12 to 18 inches between strips</li> </ul> </li> </ul> </li> </ul>
<p><b>Warranties &amp; Liability</b></p>	<p>GLUDOWN, INC. MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of any adhesive in a particular application. Given the variety of factors that can affect the use and performance of a GluDown, Inc. product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose for the user's method of application.</p>
<p><b>Limitation of remedies &amp; liability</b></p>	<p>If the GluDown, Inc. product is proved to be defective, THE EXCLUSIVE REMEDY, AT GLUDOWN, INC. OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE GLUDOWN, INC. PRODUCT. GluDown, Inc. shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.</p>